

BluePulse Series

KAC50DP-BC100DE

-  Safe & Reliable
-  Quick installation & User-friendly
-  Economical & Efficient

Outdoor Battery Cabinet Parameters

Technical parameters	BC100DE
Battery Type	LFP
Battery Module Capacity	5.12 kWh
Number of Modules	10*2
Total Battery Capacity	102.4 kWh
Nominal Voltage	512 V
Operating Voltage Range	448 V ~ 565 V
Charge / Discharge Rate	Max. 0.5C
DoD	90%

General parameters	BC100DE
Dimensions(WxDxH)	1100 x 1100 x2380 mm
Weight	< 1.5 T
Installation Site	Outdoor
IP Protection	IP54
Anti Corrosion Level	C4
Operation Humidity	5% ~ 95% (No Condensing)
Operation Temperature	-30°C ~ +50°C
Max. Operation Altitude	4000 m (> 3000 m Derating)
Communication Port	Ethernet; CAN
Communication Protocol	CAN; MODBUS TCP / IP
Cooling Method	Air Conditioner
Standards	IEC 62619-2017; UN 38.3; IEC 61000-6-2/4



Product Specifications	KAC50DP
PV Side	
Max. Input Voltage	1000 V
MPPT Voltage Range	350 V ~800 V
Max. Current per MPPT	36 A
Number of MPPT	3
Number of Inputs Per MPPT	2
Battery Side	
Max. Input Voltage	750 V
Min. Input Voltage	350 V
DC Voltage at Nominal Operation	500 V ~ 750 V
Max. DC Current	55 A*2
Max. DC Input Power	55 kW
Number of DC Inputs	2
AC Side (On Grid)	
Nominal AC Output Power	50 kW
Max. AC Output Power	55 kVA
Max. AC Current	80 A
Nominal AC Voltage	400 V
AC Voltage Range	340 V ~ 440 V
Nominal Grid Frequency/Frequency Range	50 / 60 Hz \pm 5Hz
THDv	< 3% (100% Load)
Adjustable PF Range	-1 (Lagging) ~ 1 (Leading)
AC Side (Off Grid)¹⁾	
Nominal AC Voltage	230 / 400 V \pm 3%; 3L+N+PE
THDv	< 3% (Linear Load)
Nominal Grid Frequency/Frequency Range	50 / 60 Hz
Nominal AC Output Power	50 kW
Max. AC Output Power	55 kVA
Efficiency	
Max. Efficiency	97.5%
Protection	
Reverse Connection Protection	Yes
DC Switch	Yes
Over-Temperature Protection	Yes
Grid Monitoring/Earthing Fault Detection	Yes
Insulation Monitoring	Yes
DC/AC Surge Protection	DC Type II; AC Type III
General Parameters	
Dimensions(WxDxH)	650 x 715 x 325 mm
Weight	75 kg
Topology	Transformerless
IP Protection	IP65
Operation Temperature Range	-25 ~ 60°C (> 45°C Derating)
Operation Humidity Range	0 ~ 100% (No Condensing)
Cooling Method	Intelligent Air Cooling
Max. Operation Altitude	3000 m
Communication Port	RS-485 / CAN
Standards	IEC 62477; IEC 61000; CE;GB/T; IEC 62109; IEC 61683; IEC 60068; IEC 61727; IEC 62116; EN 50549; VDE 4105; G 99

1) For off-grid application, STS100D or STS250D automatic switching cabinet is needed.